

Sale Name: 24th Spring Fever Machinery & More Auction

LOT 627c - H&S 5114 Rake



Description

H&S 5114 High Capacity hay rake, couple repairs noted, overall it presents well

Information from manufactures website:

- The HC5114 **HI-CAPACITY** 14-wheel rake has the raking wheels positioned ahead of the rake arms, main frame beams, and transport wheels.
- With a high and wide rear frame, there are no hang-up points or restrictions when raking the heaviest of hay crops.
- A brake band on each front gauge wheels can be easily adjusted to field conditions.
- The large, independent 7.5 mm 60" rake wheels deliver more capacity and turn slower for less tooth wear.
- Beehive-style spring suspension system allows the rake wheels to follow the contours of the ground smoothly.
- A large diameter rake wheel hub adds strength to the rake wheel dish.
- The adjustment for the ground pressure on the rake wheels allows the operator to fine-tune to fit varying conditions.
- The rake arms feature two ball bearings on each end of the arm for long life, smooth operation, and less wear than rakes with bushings.
- The windrow width adjustment is done with a hand crank and adjusts windrows from 38" to 58" width.
- Independent articulated rake beams have the flexibility to flex 3' up or 3' down.

- Limited oscillating offset tandem transport wheels ensure a smooth, level ride, even over irrigation tracks.
- Raking widths can be hydraulically adjusted in any position to a pre-determined raking width up to 28'.
- Rake wheel wind boards are standard.

Quantity: 1



<https://www.smithsalesco.com/>